

Kodak i100 Series Scanners



Take your office productivity to a new level

Kodak i100 Series Scanners have all the scanning performance and flexibility your busy office or department needs. Perfect Page Scanning delivers sharp, clean images without rescanning while our renowned SurePath paper handling minimizes jams.

Scan with confidence

- Simplex (i150) and duplex (i160) models to meet your needs
- Perfect Page Scanning allows you to scan even poor-quality documents and get great images at full speed
- Get bitonal, grayscale or color output, plus dual stream output options: bitonal and grayscale or bitonal and color
- Electronic color dropout suppresses irrelevant red, green or blue backgrounds for efficient forms processing

Easy setup and operation

- Bundled **Kodak Capture Software, Lite** supports a range of scanning features for practically any office application. Plus, you can easily upgrade to the full version of Capture Software and add more features and functionality
- SurePath paper handling is designed for smooth paper transport and virtually jam-free operation
- IEEE-1394 (**FireWire**) Interface for easy setup and image transfer (card and cable included for your convenience)
- Multi-feed detection with ultrasonic technology lets you feed a wide variety of paper types and weights
- Quiet operation
- Small footprint to fit on any desktop

Kodak Service & Support

Kodak Service & Support provides a global parts and distribution network, exceptional onsite and help desk service, and a variety of service plans to fit the way you work.



And you get peace-of-mind coverage with more than 3,300 certified field engineers worldwide. With **Kodak Service & Support**, the help you need is always close at hand.

Kodak i100 Series Scanners

Recommended Daily Volume	Up to 3,000 pages per day
Throughput Speeds (landscape, letter sized, bitonal, grayscale, color)	i150 (simplex): Up to 53 ppm at 150 dpi, up to 40 ppm at 200 dpi i160 (duplex): Up to 53 ppm/106 ipm at 150 dpi, up to 40 ppm/80 ipm at 200 dpi In dual stream output mode:* i150 (simplex): Up to 53 ppm/106 ipm at 150 dpi, up to 40 ppm/80 ipm at 200 dpi i160 (duplex): Up to 53 ppm/212 ipm at 150 dpi, up to 40 ppm/160 ipm at 200 dpi *scanning with simultaneous output of bitonal and color, or bitonal and grayscale, images (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)
Scanning Technology	Single Tricolor Plus CCD (i150); Dual Tricolor Plus CCD (i160) Grayscale output bit depth is 256 levels (8-bit) Color capture bit depth is 40-bit (10 bits per red, green, blue and black channels) Color output bit depth is 24-bit
Optical Resolution	300 dpi
Illumination	Single long-life Xenon lamp
Output Resolution	75/100/150/200/240/300/400/600 dpi
Maximum Document Size	297 mm x 432 mm (11.7 in. x 17 in.)
Minimum Document Size	64 mm x 89 mm (2.5 in. x 3.5 in.)
Paper Thickness and Weight	Onionskin to card stock
Feeder	Automatic document feeder for continuous loading of up to 150 sheets of 60 g/m ² (16 lb.) paper
Multi-feed Detection	Multi-feed detection with ultrasonic technology
Connectivity	IEEE-1394 (FireWire) Interface (card and cable included), 6-pin connector
Bundled Software	TWAIN and ISIS Drivers; Kodak Capture Software, Lite
Imaging Features (in the scanner)	Perfect Page Scanning, iThresholding, autocrop, aggressive crop, deskew, electronic color dropout, dual stream scanning, halftone removal, noise removal, VRS compatible
On-board Compression	CCITT Group IV; JPEG or uncompressed output
File Format Outputs	JPEG (for color and grayscale images), TIFF (for bitonal images)
Warranty (US and Canada)	One year (3 months on-site, then 9 months mail-in)
Electrical Requirements	100-240 V; 50-60Hz
Environmental Factors	Mercury-free Xenon Lamps, Operating temperature: 15-30° C (59-86° F), Operating humidity: 15 to 76 percent relative humidity
Acoustical Noise (operator position sound pressure level)	Standby mode: 38.2 dB(A) Operating mode: 53.8 dB(A)
PC Configuration	Minimum: Pentium 3 1 GHz Processor, 256 MB RAM, Recommended: Pentium 4 2.4 GHz Processor, 512 MB RAM
Supported Operating Systems	Windows 98SE, Windows Me, Windows 2000, Windows XP
Approvals and Product Certifications	UL 60950 2000-1, C-UL CAN/CSA-C22.2 No. 60950-1-03, TUV EN 60950-1:2001, CE Mark, 47 CFR Part 15 Subpart B (FCC) (Class B), ICES-003 Issue 3 (Class B), EN 55022:98 (Class B), EN 61000-3-2 Powerline Harmonics, EN 61000-3-3 Flicker, EN 55024, AS/NZS CICPR 22 (Class B) (C-Tick Mark), CNS 13438 (Class B), VCCI (Class B), CISPR 22 (Class B)
Consumables Available	Feed module, separator module, calibration targets, feeder consumables kit, extra-large feeder consumables kit
Accessories	Replaceable imaging guides, white imaging background accessory
Dimensions	Weight: i150 — 8.9 kg (19.8 lbs.), i160 — 10.4 kg (23 lbs.) Depth: 30 cm (11.8 in.) Width: 54.7 cm (21.5 in.) Height: i150 — 23.6 cm (9.3 in.), i160 — 36.5 cm (14.4 in.)

To learn more:

www.kodak.com/go/i100series

Keep it Simple. Keep it Kodak.

Printed using Kodak Technologies.



Kodak Service & Support



Eastman Kodak Company

343 State Street, Rochester, NY 14650
1-800-944-6171

Kodak Canada, Inc.

Toronto, Ontario M6M 1V3
1-800-465-6325

Kodak GmbH

Hedelfingerstr 60
70327 Stuttgart, Germany
EAMER-DI-Capture@kodak.com

©Kodak, 2007. Kodak is a trademark of Kodak.
Specifications are subject to change without notice.

Kodak (Australasia) Pty. Ltd.

Australia: 1-800-895-747
New Zealand: 0800-2 KODAK (56325)
anz-marketing@kodak.com

Kodak (Hong Kong) Limited

North Point, Hong Kong 07021
852-2564-9330

Kodak Japan Limited

Tokyo, Japan
81-3-5540-2270
jp-di-mktg@kodak.com

Kodak de Mexico

Mariano Otero 408 Guadalajara, Mexico
(52) (33) 3818-6598

For other areas outside the U.S.A.,
call +1-585-722-9287